


DP-2633

Aramid fibre with PTFE and oil Lubricant

DAIKOTE
INNOVATIVE SOLUTIONS



Style	Description	Picture	pH	TEMP °C	m/sec	Pressure bar
Style 2633 Packing	Aramid fibre with PTFE and oil Lubricant		2 - 12	-50 / +260	12	20 - Rotary (Pumps) 200 - Stationary (Valves)

Description

Style 2633 packing is a non-Asbestos packing that has been formulated especially for the replacement of Asbestos in harsh environments. Style 2633 packing is a multi-purpose packing that is most commonly used in pumps. This flexible, yet extremely tough packing works well in the harshest of applications. The product has the ability to remain soft and pliable despite very rigorous environments.

Construction

Style 2633 is a braided packing constructed of Aramid Fibre that has been braided with a liberal amount of PTFE lubricant that serves as both a blocking agent as well as a running in lubricant. Aramid fibre has the tendency to damage pump shafts, thus the need for liberal PTFE lubrication.

Application

This product is ideally suited for both reciprocating and rotary pump applications; however, it performs well in general purpose valves as well. This product is used as a general-purpose packing in water, slurry, mild acids and mild alkalis. The tough nature of the Aramid Fibre allows this packing to be used in difficult applications.

mm	3	4	5	6	7	8	10	11	12	13
inch	1/8	5/32	3/16	1/4		5/16	3/8	7/16	1/2	
m/kg	60	37	24	15	12	9,3	6	4,86	3,8	3,48
mm	14	15	16	18	19	20	22	24	25	
inch	9/16		5/8	11/16	3/4	13/16	7/8	15/16	1	
m/kg	2,95	2,6	2,3	1,8	1,61	1,42	1,2	1,03	0,92	